



BC FIBER
connect the future
B&C GROUP

1U/2U 19" & ETSI Angled Patch Panels with Telescopic Rails

Overview

Ensures professional cable management and limits the risk of health problems due to laser contact to eyes. Side facing fiber position for high laser safety.

Highlights

1U and 2U versions (12, 24, 36 and 48 port capacity)

Confirms 19" or ETSI

Professional and advanced cable management with 45 degree adaptor interface

Angled adaptor interface protects your eyes from undesired contact with laser beam coming from the adaptors-Laser safety!

Quick-stud system ensures easy closing /opening of the front cover

Easy access with telescopic rail pull-out system

Special splice cassettes of 12 or 24 port capacity with professional cable storage and protection

100% Compatible to Bellcore GR-326 standards

Confirms to every type of connectors (ST, SC, FC, LC, MTRJ, E2000, etc.)

Applications

FTTX applications, Datacenter and LAN & WAN projects.

Technical Details

Dimensions: 1U: 465 mm (W) x 238 mm (D) x 44,45 mm (H)

2U: 465 mm (W) x 238 mm (D) x 88,15 mm (H)

Material : Mild Steel

Color : Powder coat RAL7035 or RAL9005

Weight : 6 kg (2U), 4 kg (1U)

1U Patch Panel



2U Patch Panel



B&C Fiber Group duplex patch leads are manufactured in our own modern facilities from the highest quality optical fiber, terminated with ceramic ferrule connectors of various types. Cable preparation, termination and performance testing is carried out to strictly managed procedures, with high focus on quality control.

All B&C Fiber optical products are 100% optical tested and come with a test certificate. Our products are conform with all industry typical standards: **IEC, EIA, TIA or Telcordia**