



BC FIBER
connect The Future
B&C GROUP


Patch Cord duplex LC/SC/ FC/ST

OM4

Multimode
50/125 μm

LSZH

Low Smoke Zero Halogen



Connector LC / SC / FC / ST

Polishing

Return loss

Insertion loss

Ferrule material

Ferrule diameter

Insertion / extraction cycles

Multimode

UPC

≥ 20 dB

$\leq 0,30$ dB (typical)

Ceramic (zirconia)

1.25 mm / 2.5 mm

Min. 1000

Cable Mechanical Properties

Cabled optical fiber

Nominal diameter core / sheath

Color

Outer diameter

Sheath material

Bending radius (static)

Temperature range

Attenuation @ 850 / 1300 nm (dB/km)

Attenuation @ 1310 / 1383 / 1550 nm (dB/km)

OM4

50 / 125 μm

Purple

1.6 mm to 3 mm


LSZH, UL-94 V0

45 mm

-20°C +70°C

$\leq 3,2$ / $\leq 0,8$

$\leq 0,4$ / $\leq 0,4$ / $\leq 0,4$



B&C Fiber Group duplex patch leads are manufactured in our own modern facilities from the highest quality optical fiber, terminated with ceramic ferrule connectors of various types. Cable preparation, termination and performance testing is carried out to strictly managed procedures, with high focus on quality control.

All B&C Fiber optical products are 100% optical tested and come with a test certificate. Our products are conform with all industry typical standards: **IEC, EIA, TIA or Telcordia**